



ITS | untuk kejayaan bangsa

The Proceedings of

JIWECC 2010

**Japan-Indonesia
Workshop on Estuary
and Climate Change**

8 - 10 August 2010

Seminar Room, Rectorat Building
Institut Teknologi Sepuluh Nopember
Kampus ITS Sukolilo Surabaya

Organized by

Tohoku University, Japan
Institut Teknologi Sepuluh Nopember
Surabaya, Indonesia
Meteorology Climatology and
Geophysics Agency of Indonesia (BMKG)



**PROCEEDING OF
JAPAN – INDONESIA
WORKSHOP ON ESTUARY AND CLIMATE CHANGE**

8 - 10 August 2010

**Institut Teknologi Sepuluh Nopember
Surabaya, Indonesia**



Edited By:

Dr. Suntoyo

**Ocean Engineering Department
ITS Surabaya**

Organized By:

Tohoku University, Japan

Institut Teknologi Sepuluh Nopember (ITS), Surabaya, Indonesia

Meteorology Climatology and Geophysics Agency of Indonesia (BMKG)

Supported By:

Institut Teknologi Sepuluh Nopember (ITS), Surabaya, Indonesia

Society for the Promotion of Construction Engineering, Japan

Department of Ocean Engineering, Faculty of Marine Technology, ITS

ORGANIZING COMMITTEE

[Tohoku University]

Professor Hitoshi Tanaka, Dr. Eng, Tohoku University, Japan (Co-chairman)
Professor Akira Mano, Dr.Eng, Tohoku University, Japan
Professor Emeritus Masaki Sawamoto, Dr. Eng, Tohoku University, Japan
Professor So Kazama, Dr. Eng, Tohoku University, Japan
Assoc. Prof. Makoto Umeda, Dr. Eng, Tohoku University, Japan

[Institut Teknologi Sepuluh Nopember]

Professor Priyo Suprobo, PhD
Rector of the Institut Teknologi Sepuluh Nopember (ITS) (Honorary Chairman)
Professor Widi Agoes Pratikto, PhD
Department of Ocean Engineering (Chairman)
Professor Paulus Indiyono, PhD, Department of Ocean Engineering
Professor Eko Budi Djatmiko, PhD, Department of Ocean Engineering
Professor Djauhar Manfaat, PhD, Faculty of Marine Engineering
Professor Joni Hermana, PhD, Faculty of Civil Engineering and Planning
Suntoyo, M.Eng, PhD, Department of Ocean Engineering (Secretary)
Haryo Dwito Armono, M.Eng, PhD, Department of Ocean Engineering
Murdjito, MSc.Eng, Department of Ocean Engineering
Kriyo Sambodho, M.Eng, PhD, Department of Ocean Engineering

[Meteorology Climatology and Geophysics Agency of Indonesia (BMKG)]

Dr.Ir. Sri Woro B. Harijono, MSc, Chief of BMKG-Indonesia
Dr. Andi Eka Sakya M.Eng, General Scretary of BMKG-Indonesia
Drs. Soeroso Hadiyanto MSc, Deputy of Climatology Broad of BMKG-Indonesia
Dr. Edvin Aldrian, MSc, Director of Center for Climate Change and Air Quality of BMKG-Indonesia

Copyright ©2010 Dept. of Ocean Engineering, Faculty of Marine Technology
Institut Teknologi Sepuluh Nopember (ITS)
Surabaya, Indonesia
All Right Reserved

Contents

Preface

Keynote Speaker

Estuarine Hydro-& Morpho-dynamics and Global Climate Change <i>Hitoshi Tanaka (Tohoku University, Japan)</i>	1
---	---

Coastal and Estuary Hydrodynamics

Performance of an Eddy Viscosity Model for Plunging Breakers <i>Sabaruddin Rahman, Akira Mano and Keiko Udo(Tohoku University, Japan)</i>	7
--	---

Assessment of a Hydrodynamic Numerical Model with Wetting-Drying Capability <i>Purwanto Bekt Santoso, Nastain, and Wahyu Widiyanto (Universitas Jenderal Soedirman, Indonesia)</i>	13
---	----

Wave Forces On A Crown Wall Of Deep Water Berm Breakwater <i>Nurin Hidayati, Alf Tørum and Øivind A. Arntsen (Norwegian University of Science and Technology (NTNU) Trondheim, Norway)</i>	21
--	----

Defensive Effects of a Breakwater Combining Submerged Breakwater and Horizontal Plate <i>Kairi Morizawa and Yoshihiro Tsurumoto (Advanced Course of Kagawa National College of Technology, Japan)</i>	31
--	----

Vortex Shedding Analysis on Pipeline for Shallow Water <i>Esti Setiawati, Wisnu Wardana, and Suntoyo (Ocean Eng. Dept., ITS, Indonesia)</i>	37
--	----

Nearshore Morphology and Sediment Transport

Identification of River Mouth Influence on Longshore Sediment Transport in the Adjacent Beach <i>Eko Pradjoko and Hitoshi Tanaka (Tohoku University, Japan)</i>	43
--	----

Practical Formulations Of Bottom Shear Stress And Sediment Transport For Acceleration-Skewed Waves <i>Suntoyo, Hitoshi Tanaka, Bagus Afrianto and Widi A Pratikto (Ocean Eng. Dept., ITS, Indonesia)</i>	49
---	----

Sediment Modeling Level of Pemangkat's National Fishery Port (Ppn) , West Kalimantan and its Comparison with Various Alternative Conditions 55
Sadri, Purnamawati and Eko Prasetyo (Politeknik Negeri Pontianak, Kalimantan Timur, Indonesia)

The Performance of Dredging Vessel Towards Sedimentation Problem and Extreme Rainfall in Main Ship Channel Kapuas River - West Kalimantan 61
Mochammad Meddy Danial, Akhmadali and Barlian s (Tanjungpura University, Pontianak, Indonesia)

Coastal Estuarine Management and Disaster Mitigation

Study on River Mouth Clogging and its Excavation Conditions of Small River Mouth 67
Hisao Nagabayashi and Hitoshi Tanaka (Nihon University, Japan)

Theory on Saltwater in Estuary (The Second Report) 73
Mikio Sasaki, Hitoshi Tanaka and Makoto Umeda (Hachinohe Institute of Technology, Japan)

Spatial and Temporal Variations of Salinity in a Shallow Lagoon 79
Makoto Umeda, Eriko Konish, Hitoshi Tanaka and Mikio Sasaki (Tohoku University, Japan)

Observations On Beach Deformation Before And After The Indian Ocean Tsunami Around Banda Aceh Using Satellite Images 85
Syamsidik, Muzailin and Syamsul Bahri (Syah Kuala University, Banda Aceh, Indonesia)

Estimation of Discharge Through Tidal Inlet of Lake Jusan, Japan 91
Atas Pracoyo, Makoto Umeda, Hitoshi Tanaka and Mikio Sasaki (Tohoku University, Japan)

A Bacterial community shifting in a U-shape burrow of *Arenicola marina* 97
Maya Shovitri and Jens Harder (Biology Dept. ITS, Indonesia)

Study on Coral Lifeform and Species that Susceptible of Bleaching in Pltu Paiton Water 105
Dian Saptarini and Farid Kamal Muzaki (Biology Dept. ITS, Indonesia)

The Influence of Configuration of Floating Raft for Sea Weed Cultivation to Wave Reduction 113
Ho Putra Setiawan, Jumaedi Slamet (Politeknik Negeri Pontianak, Kalimantan Timur, Indonesia)

Coastal Estuarine Management and Disaster Mitigation

Salinity Intrusion Through Estuary Analysis due to Sea Level Rise using Direct Step Method (Case Study: River Banyuasin and Telang) 119
Feril Hariati (University of Ibn Khaldun, Bogor, Indonesia)

*Proceeding of Japan – Indonesia Workshop on Estuary and Climate Change 2010
August 8th -10th Surabaya, Indonesia*

Isohyets Mapping of Gerbangkertosusila Based on Noaa-Avhrr Data <i>Eko Prasetyo, Muhammad Taufik, Noer Rochma Damayanti (Class II Meteorological Maritime Perak II BMG, Surabaya, Indonesia)</i>	125
Climate Change Accelerate Coastal Erosion and Seawater Intrusion, Estuary Dam as a Shore Protection Solution, also for Drinking Water and Coastal Barrier <i>A.A.N. Agung (Bappeda Klungkung, Bali, Indonesia)</i>	131
Supply Chain Risk Management Strategies for Managing Maritime Disruptions due to the Effects of Climate Change: Evidence from the Australian-Indonesian Wheat Supply Chain <i>Saut Gurning, Stephen Cahoon and Kriyo Sambodho. (Australian Maritime College Newnham Drive, Launceston-Tasmania, Australia)</i>	137
Implementation Of Law 27/2007 About Management Of Coastal And Small Islands Region In Sidoarjo Regency And Surabaya City <i>Siti Nurlaela, Widi Agoes Pratikto, Suntoyo, Kriyo Sambodho(ITS, Indonesia)</i>	145

PREFACE

It is my great honor and pleasure to organize “Japan-Indonesia Workshop on Estuary and Climate Change” in the campus of Institut Teknologi Sepuluh Nopember (ITS), Surabaya, Indonesia on the occasion of the memorial 50th year anniversary of ITS. Since we organized previous “Japan-Indonesia Estuary Workshop” last time in Jakarta with great success in 2005, five years has passed already. After 2005, the estuary workshop has been held in various countries in Asian regions such as Hanoi and Ho Chi Minh City, Vietnam and Bangkok, Thailand. Now we come back to Indonesia again to exchange our knowledge and experiences related to estuary and climate change.

It should be mentioned here that in the year 2006, a Memorandum of Understanding (MoU) has been signed between Tohoku University and Institut Teknologi Sepuluh Nopember to promote further collaboration between two institutions. We are highly confident that this workshop will serve as an important step to accelerate further cooperation between these two universities in term of collaborative research, faculty and student exchange, joint educational program etc.

Finally, on behalf of the organizing committee of the workshop, sincere appreciation is expressed to all authors contributing to our workshop. Special thanks are also due to all keynote speakers and chairpersons for the efforts in preparing the manuscripts and managing the sessions, respectively.

With best wishes,



Prof. Hitoshi TANAKA, PhD
Chairman of the Organizing Committee
of the Japan-Indonesia Estuary Workshop
Department of Civil Engineering
Tohoku University
Japan.



Prof. Widi Agoes Pratikto, PhD
Chairman of the Organizing Committee
of the Japan-Indonesia Estuary Workshop
Department of Ocean Engineering,
Institut Teknologi Sepuluh Nopember
Indonesia.

THE PERFORMANCE OF DREDGING VESSEL TOWARDS SEDIMENTATION PROBLEM AND EXTREME RAINFALL IN MAIN SHIP CHANNEL KAPUAS RIVER - WEST KALIMANTAN

MOCHAMMAD MEDDY DANIAL¹⁾, AKHMADALI²⁾ STEFANUS BARLIAN S.³⁾

- 1) Civil Engineering, Tanjungpura University
Pontianak, Indonesia
e-mail: meddystmt@yahoo.com
- 2) Civil Engineering, Tanjungpura University
Pontianak, Indonesia
e-mail: akhmadali2002@yahoo.com
- 3) Civil Engineering, Tanjungpura University
Pontianak, Indonesia
e-mail: mr.barlian@yahoo.com

Abstract

Main ship channel of Kapuas river is one of the most strategic infrastructure in West Kalimantan. Every year, the entrance of Kapuas river faces the sedimentation process and siltation. The extreme rainfall also can give some problem toward the dredging work. Regular maintenance is conducted by using dredging method with Trailing Suction Hopper Dredge type with hopper volume is 1500 m³. This research is to analyse and evaluate the performance of dredging vessel during 180 days. The method is using parameter relation between distance, time and speed of dredging vessel performance. Goal seek is used to enable the performance of dredging vessel to fulfill the progress of dredging work.

The result shows that dredging vessel has no good performance where the vessel speed is only 3-4 knot and causes time delay 6 – 9 months longer. The dredging vessel should have a speed of at least 7 knot. To overcome the problem due to vessel speed and extreme rainfall, the additional dredging vessel is required to fulfil time schedule with minimum speed and volume of 7 knot and 1800 – 2500 m³ respectively.

1. INTRODUCTION

Kapuas river is important for various purposes. The most important purpose is to navigation channel and shipping transportation in West Kalimantan. Kapuas river is also as the shipping channels provide access to the port of Dwikora, Pontianak. Port of Dwikora is the largest port with total area 96.789 m², eight piers and it can contain 2000 containers.

The length of shipping transportation channel between Dwikora Port and river mouth is about 22.1 km with range of channel width between 40 m – 80 m and time travel of ships between Dwikora port and outer channel in the river mouth is about 2 hours. The channel width in the front of Dwikora port is quite wide about 200 m – 300 m.

Not along shipping channel experience siltation and the sedimentation process usually occurs and concentrated in the mouth of Kapuas river and cause shoaling of river mouth. So the river mouth, especially in navigation channel need to deepen in order to ensure ongoing safe ship passage every year. Pelindo II is a stakeholder that have authority and responsibility to conduct the dredging work to maintain the shipping channel almost every year due to the sedimentation process that can cause a shallow location of river channel.

One of the threat for dredging work is extreme rainfall condition, where usually occurs during rainfall period especially between August and October. Due to extreme rainfall problem, the dredging work become more difficult and can cause delay for finished it as on time. In the future, the effect of climate change such as extreme rainfall and extreme river discharges could give some bad influence toward sedimentation problem and shoaling of entrance ship main navigation in Kapuas river (Laboyrie, P. 2009).

2. DATA AND METHODS

Navigation channel for shipping transportation in Kapuas River has width of channel 60 m and water depth -4.0 m of low water spring (LWS). The length of navigation channel that should be dredged is about 8.5 km. Disposal site is located at coordinate UTM 49 N 277405 3687 where the water depth is -20 m LWS. The distance between disposal site and dredging location is about 11.5 km (Pelindo,2009).



Source: MapSource 6.15.6

Figure. 1. Area of dredging works

The dredging vessel type is Trailing Suction Hopper Dredge (TSHD) whereas the specification of hopper capacity and vessel speed is 1500 m³ and 8 knot, respectively. This dredger works by pumping the dredged material into a hopper contained within the dredger. When the hopper is full the dredger sails to the dredged material disposal site and deposits the dredged material via opening doors in the bottom of the hull (Nicol, G., 2002).

Dredging work is conducted during six months or 180 days. It is important to be known that the total time of dredging works is still reduced by survey of bathymetry after finishing the dredging works, final calculation of dredging volume and confirmation by the stakeholder or Pelindo II. So, the total of dredging works is only about 165 days (Pelindo, 2009).

Method to analyse performance of dredging vessel is using parameter correlation between distance (S), speed (V) and time (T) from simple equation as follows:

$$S = V \times T \quad (1)$$

From Equation 1, the actual result of vessel speed performance is compared with the speed of dredging vessel based on the specification data. If actual speed value of vessel less than specification

data of vessel speed, then the vessel speed performance is not good due to under performance. On the contrary, if actual speed of vessel equal than specification data of vessel, the vessel speed performance is very good.

To analyse the minimum speed of vessel is used the goal seek method using Equation 1. Goal seek is a what-if analysis tool and solving function invers problem single. Goal seek is useful to determine unknown value of travel time of dredging vessel based on the known value of vessel speed.

The capacity of hopper is 1500 m³ and each dredged material pumped into a hopper should not contain 100% of dredged material of river, so that the total material in the hopper also contain some other material such as water, garbage, and etc. From this condition, the dredged material must be estimated using coeficient parameter. In this research, coeficient parameter is determined as reduction factor. The reduction factor is 0.5, so that the real of dredged material in hopper is about 0.5 x 1500 m³ or 750 m³ every one trip.

Table 1 shows the analysis to finish dredging work to deepen the main ship channel. This analysis assume that all condition is normal without some disturbances such as extreme climate, heavy rain, storm wave, etc. This analysis is also not consider that the vessel could be damage due to some problems. If the dredging vessel experience damage, the time schedule must be corrected and must be analysed to overcome the problem.

Table 1. Finish Analysis of Main Ship Channel Dredging Work

Capacity volume of Hopper	1500	m ³
Coeficient reduction	0.5	coef.
Dredged volume /Trip	750	m ³
Amount of trip /day	6	Trips
Dredged volume /day	4500	m ³
Total time to finish dredging work	159.3862	days
Total Time schedule of dredging work	180	days
Final sounding and calculation of final volume of dredged material	15	days
Effective time to dredging work	165	HARI
Remain of days	5.613777778	
Conclusion	On schedule	

3. RESULTS AND DISCUSSIONS

The performance of dredging vessel speed can be analysed using parameter relation between distance, speed and time. Each performance of vessel speed is devided with three condition, namely loading time condition, shipping to disposal area or dumping area (DA), and unloading condition.

Loading time condition is time that be required from starting to dredge until hopper volume capacity is fulfilled. Shipping to disposal area or dumping area is a condition where the dredging vessel transporting the sediment material lead to dumping area (DA). Unloading condition is a condition where dredging vessel already disposed of at certain location that has been determined.

Table 2. Performance of Dredging Vessel Benco 5 Capacity 1500m³ for one cycle trip

Dredging works	Mean of Loading time / day (minute)	To Disposal Area/day (menit)	Mean of Off-Loading time / day (minute)	Total time of dredging cycle (minute)	Total time of one dredging cycle (hour)
Week- 7	46.80	110.32	93.45	250.57	4.18
Week- 8	55.48	150.71	122.95	329.14	5.49

Source: PT. Trimulia Re kayasa Utama. (2009)

Based on the evaluation report of dredging for daily and weekly respectively, it can be seen that dredging vessel performance only can achieve about 4 – 5 hours in each cycle trip (See Table 2). Table 3 shows that the vessel speed performance at loading condition, sailing to dumping area and sailing from dumping area of 1.98 knot, 3.64 knot, and 4.5 knot respectively.

It can be seen that vessel speed performance at loading condition or dredge condition is quite slow with 1.98 knot, whereas at condition of sailing to dumping area, the vessel speed is increase become 3.64 knot and at condition where the hopper is empty or at sailing back to dredging site, the vessel speed is more increase with 4.5 knot.

Table 3. Performance of Dredging Vessel Speed at each condition

Weekly Report	Vessel speed at Loading Time (knot)	Vessel speed at Sailing to DA (knot)	Vessel speed at Off-loading/Sailing from DA to spot (knot)	Note
Week -7	1.96	3.79	4.63	mean speed
Week- 8	1.99	3.48	4.38	mean speed
	1.98	3.64	4.50	mean speed

Source: Source: PT. Trimulia Rekayasa Utama. (2009)

Because the dredging work does not work in good performance due to vessel speed, then a minimum speed of vessel must be analyzed to be able to finish the dredging work on schedule. Using goal seek tool, the minimum speed of dredging vessel can be calculated easily using parameter speed (V), distance (S) and time (T).

Steps to get the minimum speed of dredging vessel is determine the speed of vessel as known variable, then using goal seek, the time (T) as a parameter function related to the speed and distance can be calculated. Note that speed is a function of distance divide time. Analysis of goal seek to seek the fastest time can be seen in Table 4. Table 4 shows that mean of time travel in every one cycle of dredging work only need about 2.7 – 2.8 hours if the vessel speed could achieve 7 knot.

Table 4. Performance Analysis of Dredging Vessel Speed/cycle with 7 knot

No.	Location Segment	Distance (meter)	Time Travel		Time unit
1	Spot 40 - 75	2500 - 4000	11	15	minute
2	Spot 75/80 to DA	16500 - 17000	76	77	minute
3	DA to Spot 75/80	16500 -17000	76	78	minute
			163	170	minute
			2.72	2.83	hours

From Table 4, we then can confirm that the minimum speed of dredging vessel is about 7 knot to achieve one cycle of dredging work in 3 hours. This speed of dredging vessel is already including influencing factors that can give some impact for delay of time schedule such as extreme rainfall and other disturbance during operation of dredging work. From Table 4, we then can make a fomula like in Table 5 to analyse trip amount in one day (24 hours). The result shows that dredging work is able to achieve 6 trips with total time is about 18 hours as can be seen in Table 5.

Table 5. Analysis of trip amount with dredging vessel speed 7 knot

Amount of trip	Time length	
1 trip	3	hour
5 trip	15	hour
6 trip	18	hour

Besides the problem of vessel speed that not in good performance, there is some other problem occur during the dredging work, namely the dredging vessel has experience damaged such as the suction pump and components of pump. Total time of dredging work that did not operated is about 40 days.

Table 6 shows the implication of damaged of vessel toward time delay in relation to finishing dredging work on time. The result shows that time delay can cause additional time more than 6 months until 9 months. Besides that, the remaining volume of dredged material at eight weeks is still achieve 26.652 m³ (4%).

Table 6. Finished analysis of main ship channel dredging work due to damaged of vessel

Dredged volume at week 8	26.652.56	m ³
Remaining volume that not yet be dredged at week 8	690.585.44	m ³
Volume capacity of Hopper	1.500.00	m ³
Coefficient reduction	0.5	coef.
Dredged volume /Trip	750.00	m ³
Amount of trip /day	3	trips
Dredged volume /day	2.250.00	m ³
Time estimation of dredging work based on remain volume that not yet dredged	306.93	days
Total Time schedule of dredging work	180	days
Final sounding and calculation of final volume of dredged material	15	days
Remain of effective time to dredging work	108	days
Remain of days due to total delay	198.92686	days
Remain of months due to total delay	6.63089535	months
Conclusion	Delay	

Remaining volume of 447.585 m³ in Table 7 is at condition where dredging works has achieved fifth month or sixteenth weeks, so that only about 38% from dredging work progress. Table 7 shows that additional vessel is required in order to fulfil time schedule of dredging work. The second vessel with same hopper capacity is able to overcome the remain of time delay of dredging work so that can finishing the dredging work on time.

Table 7. Finished Analysis of Main Ship Channel Dredging Work Due To Second Vessel

Remaining volume of dredged material due to delay from first vessel	447.585.44	m ³
Volume capacity of Hopper	1.500.00	m ³
Coefficient reduction	0.5	coef.
Dredged volume /Trip	750.00	m ³
Amount of trip /day	6	trips
Dredged volume /day	4.500.00	m ³
Time estimation of dredging work based on remain volume that not yet dredged by first Vessel	99.46	days
Total time schedule of dredging work	180	days
Final sounding and calculation of final volume of dredged material	15	days
Remain of effective time to dredging work	108	days
Remain of days due to total delay	8.5365698	days
Remain of months due to total delay	0.28455233	months
Conclusion	OK-On Schedule	

4. CONCLUSIONS

1. The result shows that dredging vessel has no good performance because of the vessel speed is only 3 - 4 knot.
2. The time needed to achieve one cycle trip of dredging and disposal work is about 5 hours so that in one day, there is only 3 or 4 cycle or trip.
3. Vessel damaged can cause the implication toward time schedule of dredging work. The impact can cause additional time about 6 – 9 months if there is no.
4. From the results, the dredging vessel should has vessel speed about 7 knot per trip.
5. Additional vessel of dredging is required in order to fulfil the time schedule of 180 days with the spesification of dredging vessel should has speed and hopper volume of 7 knot and 1500 m³ – 2500 m³, respectively.
6. In the future, the dredging works must face the effect of climate change and some preparation should be done to overcome the problem that will rise.

5. ACKNOWLEDGEMENTS

I would like to thanks to PT. Pelindo II Pontianak, Consultant Engineering PT. Trimulia Rekayasa Utama, and Contractor PT. Mekarjaya Abadipratama as partner for dredging works of Main Ship Channel Kapuas River Pontianak West Kalimantan.

6. REFERENCES

- Laboyrie, P. (2009). Dredging for Climate Change and Transport in the Netherlands: Dredging to Survive. Hydr&Env Eng RWS, Ministerie Van Verkeer en Waterstaat.
- Nicol, G.(2002). Channel Maintenance Dredging. Victorian Channel Authority
- Pelindo.(2009). Report of Pre-dredge Sounding of Dredging Works of Main Ship Navigation of Pontianak Port, Pontianak
- PT. Trimulia Rekayasa Utama. (2009). Monthly Progress Report of Dredging Works of Main Ship Navigation of Pontianak Port, Pontianak
- PT. Trimulia Rekayasa Utama. (2009). Analysis of Progress Sounding of Dredging Works of Main Ship Navigation of Pontianak Port, Pontianak
- <http://www.benco.com.sg/benco5.htm>